

Industrial Mobile Safety Steps - Manufactured in Ireland

Strong, Safe, Manoeuvrable with anti-slip ribbed rubber covered treads.

The Mobile Safety Step is a welded product, as such, it cannot be certified. In EU Law this is treated as a machine not a ladder.

Materials of Construction

Main frame & back support frame: 50mm x 25mm box section zinc steel

Guard Rail: 25mm tubular steel

Step/ Platform: Pressed steel [2mm] with well recess and fitted with anti-slip rubber mats.

Specification

Platform area: Standard size 533mm x 410mm [WxD]

Step tread area: Standard size 533mm x 203mm [WxD]

Platform Cage: Rising 1000mm above platform deck

Standard Equipment:

Handbrake: Hand operated lever brake using 2 castors 75mm diameter

Rear frame: Fitted with 2 fixed direction 200mm solid wheels

Optional Equipment:

All swivel Wheels: A second set of swivel wheels fitted to rear of step unit to facilitate steering around confined spaces. (these swivel wheels are operated by a lever and are fitted in conjunction with the standard wheels)

Step/Platform surface: Aluminium chequer plate non-slip treads can be fitted in place of rubber matting.

Sizes/Dimensions in mm:

Code:	Length:	Width:	Height:	Platform Height:	Reach from Platform:***	No. of treads:
MST3P	710	860	1680	680	2180	3
MST4P	842	860	1910	905	2405	4
MST5P	974	860	2140	1130	2630	5
MST6P	1106	900	2370	1355	2855	6
MST7P	1238	900	2600	1580	3080	7
MST8P	1370	900	2820	1805	3305	8
MST9P	1502	900	3050	2030	3530	9
MST10P	1634	900	3280	2255	3755	10
MST11P	1766	950	3510	2480	3980	11
MST12P	1898	950	3740	2705	4205	12
MST13P	2030	950	3970	2930	4430	13
MST14P	2162	950	4200	3155	4655	14
MST15P	2294	950	4420	3380	4880	15
MST16P	2426	950	4640	3605	5105	16

***Reach height is considered to be 1500mm above platform

Notes:

All models are available with: Walk-off to rear/ Walk-off to left/ Walk-off to right.

Platform depth can be extended from 410mm to: 508mm/711mm/914mm.